



Republic of the Philippines

Inlang Cavite, Philippines
 (046) 889 6373
www.csueduph

1. The Cavite State University (CSU) invites interested firms/supplier to submit quotation for the project
 with an Approved Budget for the Contract (ABC)
 Quotation received in excess of the ABC shall be automatically rejected at the opening

1	1	Pc	Network Cable Comb 24 Holes Network Cable Comb for Cat6	2,000.00	2,000.00
2	2	Pcs	Bar Code Scanner Omni directional 2D Image scanning LED light alarm, Buzzer alarm Read speed: 2500 times/sec Resolution: SXGA (W1280 H 1024) Ratio (5:4) Scanner type: Mini Code, Micro PDF417, MSI code, PDF417, Planet, Plessey Code, Postnet, QR code, RSS, Standard 2 of 5, Telepen, TLC 39, UPC/EAN, etc Voltage: DC+5V ±5% or +3.3V ±5% Interface: USB (drive free, Virtual) RS232 Install drive, Drive Free Dimension (L*W*H): 110mm x 124mm x 152mm Weight: 450g Color: Black Material: PC	8,400.00	16,800.00
3	4	Units	walkie talkies Voltage: 7.5V DC Distance: 15km (10 mile) VHF 2pc (set) radio dust and waterproof Frequency range: TX/RX guaranteed range TX: 144.148MHz; RX: 136.174MHz Type Emissions: F2DF3E (FMFMN) Number Channels: 207 channels (200 call edges); Antenna Impedance: 50	9,000.00	36,000.00
4	20	Units	Automatic Voltage Regulator 220VAC Voltage Range: 220VAC 184.276VAC Frequency: 50/60Hz Output: 220 Voltage: 208-253 VAC	555.00	11,100.00

5	1	Unit	Desktop Computer CPU: Intel i3 10105, 4 cores 8 threads up to 4.4GHz; RAM 8gb DDR4 Storage: 500GB SSD GPU: Integrated Intel HD Graphic PSU: 80+ Certified WiFi: Ac 1600 OS: Licensed Windows 11 Home Licensed Microsoft Office 2021 Home & Student 1 Year Warranty	30,000.00	30,000.00
6	1	Unit	Camera Video Mixer Switcher Video inputs: HDMI Type A x4, RGB/COMPONENT (Mini D sub) x1, Composite RCA Phono x1 Video output: HDMI x2, RGB/COMPONENT (Mini D sub) x1, USB 3.0 (B type) Audio Input: XLR/TRS combo type, phantom power x4, RCA Phono x2, Stereo mini 3.5mm x2, USB B type (stereo) Audio Output: XLR (L, R), RCA Phono (L, R), USB B type (stereo), Stereo mini 3.5mm Resolution/refresh rate: 1920x1200/60Hz Max audio rate/bit depth: 48kHz, 24bit	15,000.00	15,000.00
7	1	Unit	Touchscreen LCD Monitor LCD panel type: TFT LCD (TN) Backlight type: WLED system Panel Size: 21.5 inch / 54.6 cm Effective viewing area: 476.61 (H) x 268.11 (V) Resolution: 920x1080 @ 60Hz Touch technology: Projected capacitive OS: Windows 10/8.1/8/7, Android 7.1/7.0/6.0/5.0/4.4; certain Linux versions 1 year Warranty	20,000.00	20,000.00
8	10	Units	RJ45 LAN coupler high quality	6000	60000
9	5	Units	UPS, 650VA, 390W, Output Sockets: 4 Battery: 1 x 12V/7Ah Multifunction Printer PinP	2,500.00	12,500.00
10	5	units			

M tn
Q PH

indicate the brand and model of the items being offered

4 Warranty shall be for a period of six (6) months for supplies and materials. Warranty for